

# CLEANING SEALING & AFTERCARE

## CEMENT, GROUT & SALT RESIDUE REMOVER TECHNICAL DATA SHEET

REF 38/5/1 SEPT 2018



### LTP CEMENT, GROUT & SALT RESIDUE REMOVER

#### Interior & Exterior use

For all types of **Unpolished Natural Stone** can also be used on porcelain, glazed ceramic, slate, quarry tiles, brick, terracotta and granite.

A rapid action cleaning agent for removing cement residues, grout stain, salts, efflorescence and other similar deposits. May also be used in dilute or concentrated form.

#### Directions for use

For application and cleaning tools see LTP website.

Always test/practice on an inconspicuous area before proceeding to ensure that the finished result is satisfactory.

Shake container well before use.

#### In mild cases and on non-absorbent surfaces:

Dilute 1 part LTP Cement, Grout & Salt Residue Remover in 4 parts cool water. Apply with a cloth or sponge wrung out in the solution. Leave for up to 30 minutes. Extract released residues using a sponge and water.

#### In more severe cases:

Dilute 1 part LTP Cement, Grout & Salt Residue Remover in 1 part cool water. Apply liberally and spread over surface. If necessary, agitate with a scrubbing brush or rotary scrubbing machine and leave to react for 5-10 minutes, keeping wet surfaces wet with additional LTP Cement, Grout & Salt Residue Remover solution. Extract and rinse thoroughly with clean water.

#### In extremely severe cases:

Wet the surface to be cleaned and apply undiluted. Agitate with a nylon pad, scrubbing brush or mechanical scrubber. Immediately extract and rinse thoroughly with clean water.

**N.B.** Always dilute by adding product to water. Not the other way round. Always rinse surfaces thoroughly with cool clean water.

#### Coverage

Approximately 5-25m<sup>2</sup> per litre.

#### Storage information

Store in a cool, dry, frost free environment ideally at 5 - 25°C  
Shelf life up to 2 years if container is unopened.

#### Notes

Not suitable for use on surfaces that are **polished, (i.e. polished marble, travertine or limestone)**. Any contaminated surface should be rinsed off immediately with plenty of **clean water**. Do not use when under floor heating systems are in operation. Mask and protect any surface not to be cleaned.

#### Health, Safety & Environmental

**Causes skin irritation. Causes serious eye damage.**

Keep out of reach of children. Read label before use.

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection. **IF ON SKIN:** Wash with plenty of water/soap. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor

If skin irritation occurs: Get medical advice/attention. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.



**DANGER**



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [info@ltp-online.co.uk](mailto:info@ltp-online.co.uk)  
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK

